

COUNTERBALANCED

4-wheel engine trucks torque converter



M315 - 318

- 1.5 t - 1.8 t
- 7470 mm
- DIESEL / LPG

M320 - 325

- 2.0 t - 2.5 t
- 7470 mm
- DIESEL / LPG

M330 - 335

- 3.0 t - 3.5 t
- 7470 mm
- DIESEL / LPG

4-wheel engine trucks hydrostatic



Drago 150 - 200

- 1.5 t - 2.0 t
- 6170 mm
- DIESEL / LPG

Drago H 250 - 300 - 350

- 2.5 t - 3.0 t - 3.5 t
- 7960 mm
- DIESEL / LPG

Drago E 250 - 300 - 350

- 2.5 t - 3.0 t - 3.5 t
- 7960 mm
- DIESEL / LPG



Drago 400 - 450 - 500

- 4.0 t - 4.5 t - 5.0 t
- 6650 mm
- DIESEL

SID-P 60 - 70 - 80

- 6.0 t - 7.0 t - 8.0 t
- 5530 mm
- DIESEL

CESAB PRODUCT RANGE

Counterbalanced and Warehouse Equipment



© 2018. All rights reserved. Availability and specifications are determined locally and are subject to change without notice. Please consult your authorized CESAB distributor for further details. 168 01111



COUNTERBALANCED

3-wheel electric trucks



| BIT 800 - 1000 - 1200 | | B210 - 213 - 215 | | B315 - 316 - 316L - 318 - 318L - 320 | |
|-----------------------|-----------------------|------------------|------------------------|--------------------------------------|-------------------------------|
| | 0.8 t - 1.0 t - 1.2 t | | 1.0 t - 1.25 t - 1.5 t | | 1.5 t - 1.6 t - 1.8 t - 2.0 t |
| | 5965 mm | | 6470 mm | | 7470 mm |
| | 24 V / 800 Ah | | 24 V / 1000 Ah | | 48 V / 750 Ah |

4-wheel electric trucks



| B415 - 416 - 416L - 418 - 418L - 420 | | Blitz 250 - 300 - 300L - 350 | | Mak 400 - 450 - 500 | |
|--------------------------------------|-------------------------------|------------------------------|-----------------------|---------------------|-----------------------|
| | 1.5 t - 1.6 t - 1.8 t - 2.0 t | | 2.5 t - 3.0 t - 3.5 t | | 4.0 t - 4.5 t - 5.0 t |
| | 7470 mm | | 7160 mm | | 7450 mm |
| | 48 V / 750 Ah | | 80 V / 775 Ah | | 80 V / 775 Ah |

Compact electric trucks



| centTAURO 48 160L - 200L | | centTAURO 80 250 - 300 | | B860 - 870 - 885 | |
|--------------------------|---------------|------------------------|---------------|------------------|-----------------------|
| | 1.6 t - 2.0 t | | 2.5 t - 3.0 t | | 6.0 t - 7.0 t - 8.5 t |
| | 6970 mm | | 6860 mm | | 6450 mm |
| | 48 V / 840 Ah | | 80 V / 735 Ah | | 80 V / 1050 Ah |

Heavy duty electric truck



WAREHOUSE EQUIPMENT

Hand pallet trucks



| CE200 - 230 - 300 | | CE200ST | | CE100HL - 100HLE | |
|-------------------|---|---------|-------------------------|------------------|--------------------------------------|
| | 2.0 t - 2.3 t - 3.0 t | | 2.0 t | | 1.0 t |
| | | | | | 810 mm |
| | The 2.3 t model is also available with low forks, quicklift feature and handbrake. Low forks are standard on the 2.0 t model. | | Stainless steel version | | Manual and electric scissor lifters. |

Powered pallet trucks



| P113 | | P214 - 216 - 218 - 220 - 225 | | P320 - 324 | |
|------|--------------|------------------------------|--|------------|--|
| | 1.3 t | | 1.4 t - 1.6 t - 1.8 t - 2.0 t - 2.5 t | | 2.0 t - 2.4 t |
| | 24 V / 63 Ah | | 24 V / 150 - 300 Ah | | 24 V / 300 - 620 Ah |
| | | | Optional operator platform available for P220. | | The P320 is also available as a high performance version (8.5 km/h). The P324 is also available with power steering. |

Reach trucks



| R212 - 214 - 216 | | R314 - R316 - R318 - R320 - R325 | | Trac E 50 | |
|--|-----------------------------|---|--|-----------|---------------|
| | 1.2 t - 1.4 t - 1.6 t | | 1.4 t - 1.6 t - 1.8 t - 2.0 t - 2.5 t | | 5.0 t |
| | 6000 mm - 6300 mm - 8500 mm | | 9000 mm - 10500 mm - 11000 mm - 12500 mm | | 1000 N |
| | 48 V / 620 Ah | | 48 V / 620 - 930 Ah | | 40 V / 275 Ah |
| Also available as a cold store version as well as drive-in version with narrow overhead guard. | | Also available as a cold store version, with or without heated cabin, as well as a drive-in version with narrow overhead guard. | | | |

Powered stacker trucks



| S110 - 110S | | S208L | | S210 - 212 - 214 | | S212S | |
|-------------|--------------------------------------|-------|--|------------------|---------------------------------------|-------|---|
| | 1.0 t | | 0.8 t | | 1.0 t - 1.2 t - 1.4 t | | 1.2 t |
| | 1960 mm - 2000 mm | | 1580 mm | | 3300 mm - 4500 mm - 4755 mm | | 4755 mm |
| | 24 V / 63 Ah | | 24 V / 230 Ah | | 24 V / 225 - 300 Ah | | 24 V / 300 Ah |
| | S110S: straddle support arm version. | | Can lift up to 2000 kg when lifting with the support arms only. Available with optional automatic height adjustment. | | Optional operator platform available. | | Straddle support arms. Optional operator platform also available. |



| S212L - 214L | | S220D | | S313 - 316 - 320 | | S313L - 316L - 320L | |
|--------------|---|-------|---|------------------|--|---------------------|--|
| | 1.2 t - 1.4 t | | 1.0 t | | 1.25 t - 1.6 t - 2.0 t | | 1.25 t - 1.6 t - 2.0 t |
| | 4500 mm - 4755 mm | | 2100 mm | | 3950 mm - 5400 mm | | 3950 mm - 5400 mm |
| | 24 V / 300 Ah | | 24 V / 300 Ah | | 24 V / 425 Ah | | 24 V / 425 Ah |
| | Elevating support arms. Optional operator platform available (see image above). | | Double stacker, lifts 800 + 1200 kg lifting with forks + support arms or 2000 kg when lifting with the support arms only. | | Also available as a walkie version (without platform and longer tiller arm). | | Elevating support arms. Also available as a walkie version (without platform and longer tiller arm). |

Towing tractor



| S314S | | Legend | |
|---|---------------|--------------------------|-----------------------|
| | 1.35 t | Rated capacity | Additional info |
| | 5400 mm | Maximum lifting height | Fuel type |
| | 24 V / 425 Ah | Maximum battery capacity | Nominal draw-bar pull |
| Adjustable straddle support arms. Also available as a walkie version. (Without platform and longer tiller arm.) | | | |